















Our lift-slide doors are dedicated for people who value funcionality and comfort. Use of advanced technology allows us to produce sliding doors up to 18m wide and up to 3m high.

Regardlessof the dimension of the lift-slide door, the sashes slide smoothly and with ease; locking and unclocking the sashes does not require any effort.

Sliding balcony door is available in two versions: double pane (68 system) and triple pane (88 system). Presented technical data concerns 88 system version.



Standard

Sliding balcony door

⊕ TECHNICAL DATA



	Material	Engineeredfingerjointed pine, selected pine, meranti, oak, other on request, laminated.
Uw	Uw value	0.69 W/m²K (for test sizewindow = 4000 x 2500 mm)
	Glazing packages, Ug value	26mm (4-18-4), Ug= 1,1 W/m²K/ 32mm (4-10-4-10-4), Ug= 0,8 W/m²K48mm (4-18-4-18-4), Ug= 0,5 W/m²K/ 54mm (6-18-6-18-6), Ug= 0,5 W/m²K Glass package may be modified.
	Air permeability	Class 4
000	Watertightness	Class E750
ವಿ	Wind load	Class C2
4	Fittings	Siegenia Comfort
7	Surface treatment	Transparent colours based on current colour chart. Opaque colours based on RALand NCScharts.
	Aluminium claddings	Powder coated colours based on RALchart (by Qualicoat sign, licence number: 1515).

OPENING DIAGRAMS



