











Our exterior doors IV 68 are produced from engineered fingerjointed wood and have very solid, stable construction. They constitute a showcase of a house they protect.

Each door is manufactured to individual order. Customers can choose their own model out of about 40 factory patterns or provide their own design. As with all manufactured goods, we offer a wide range of transparent and opaque colours.

Our exterior doors by stand for great design, strong construction and very good parameters. Our doors are a long-term investment.



External door 68



TECHNICAL DATA

	Material	Engineered fingerjointed pine, selected pine, meranti, oak, other on request, laminated.
	Frame construction	Section 68 x 81mm
	Standard leaf construction	Sash section 68x120mm (Classic, Modern models) Door filling - Stadur panel Sash with moulding beads on one side or double-side. All technically possible shapes and sizes available.
	Flat panel leaf	Flat sash - Variotec panel - Deco models. All technically possible shapes and sizes available.
	Glazing package	Double pane glass (4-18Ar-4), Ug value = 1,1 (PN-EN 673) Ornamental glass, safety glass, solar control glass - option. Warm edge spacer - option. Glass package may be modified.
$\langle \cdot \rangle$	Air permeability	Class 4
000	Watertightness	Class 4
Ē	Fittings	Winkhouse flat lock; A or C class patent lock inserts; Simonswerk Protect 3D hinges; concealed hinges - Siegenia Axxent.
	Thresholds	Aluminum thresholds Gutmann, Weser New, Dafa; composite threshold ULT
7	Surface treatment	Transparent colours based on current colour chart. Opaque colours based on RAL and NCS charts.

