



## Wooden doors

# External door 92



🇬🇧 Exterior doors IV 92 are dedicated for energy-efficient buildings. Clever design allows for producing doors with excellent heat transfer coefficient and acoustic insulation.











Each door is manufactured to individual order. Customers can choose their own model out of about 40 factory patterns or provide their own design. As with all manufactured goods, we offer a wide range of transparent and opaque colours.

Exterior doors by Słowiński stand for great design, strong construction and very good parameters. Our doors are a long-term investment.

# External door 92



 TECHNICAL DATA

	<b>Material</b>	<i>Engineered fingerjointed pine, selected pine, meranti, oak, other on request, laminated.</i>
	<b>Frame construction</b>	<i>Single frame 92 x 81mm</i>
	<b>Standard leaf construction</b>	<i>Sash section 68x120mm (Classic, Modern models) Door filling - Stador panel Sash with moulding beads on one side or double-side. All technically possible shapes and sizes available.</i>
	<b>Flat panel leaf</b>	<i>Flat sash - Variotec panel - Deco models. All technically possible shapes and sizes available.</i>
	<b>Glazing package</b>	<i>Triple pane glass (4-18Ar-4-18Ar-4), Ug value = 0,5 (PN-EN 673) Ornamental glass, safety glass, solar control glass - option. Warm edge spacer - option. Glass package may be modified.</i>
	<b>Air permeability</b>	<i>Class 4</i>
	<b>Watertightness</b>	<i>Class 4</i>
	<b>Fittings</b>	<i>Winkhouse flat lock; A or C class patent lock inserts; Simonswerk Protect 3D hinges; concealed hinges – Siegenia Axxent</i>
	<b>Thresholds</b>	<i>Aluminum thresholds Gutmann, Weser New, Dafa; composite threshold ULT</i>
	<b>Surface treatment</b>	<i>Transparent colours based on current colour chart. Opaque colours based on RAL and NCS charts.</i>

