irei | manuela frei pict

Technical alterations are subject to change | 04/2008

GB |

aluplast GmbH | Kunststoff-Fenstersysteme

Auf der Breit 2 | D-76227 Karlsruhe | Tel. +49 (721) 47171-0 Fax +49 (721) 47171-999 | info@aluplast.de | www.aluplast.de



Windows let light into the rooms and protect against external effects. IDEAL 4000® from aluplast offers the perfect synthesis of innovative window technology and vitality for life.

Heat insulation | for energy conscious living

aluplast window system orivide the best heat insulation characteristics at all times for a comfortable room atmosphere.



IDEAL 4000[®] advantages for you

- · 70 mm depth
- · heat insulation characteristics for the standard combination U_{f} -value = 1.3 W/m²K
- · glazing thickness up to 43 mm
- · sound insulation up to 46 dB (up to sound insulation class IV)
- · double design variety in the sash (surface offset | half-surface offset)
- · different profile shapes for an individual design
- · design glazing bead for the interior
- · covered, non-visible drainage possible
- · 5 chamber system as standard combination
- · continuous groove seal system in the frame and sash
- · use of the relevant security window hardware guarantees outstanding protection against break-in



Sound insulation | pure relaxation

in your own four walls.

Noise is unpleasant and has a negative effect on the human body. aluplast U-PVC window systems guarantee the best insulating properties in the window profile.











Security | thanks to IDEAL 4000®

Burglar resistant window profile constructions provide more security