













Scandinavian outward opening windows have been developed in view of recipients from the Northern Europe where this type of joinery is the most popular.

Their carefully designed, slim construction gives the impression of simplicity and sublime elegance. The use of high quality materials (engineered wood, technically advanced fittings, heat protection glazing units) and modern production technology allows obtaining a product with excellent aesthetic and functional parameters.



Flush Casement

Outward opening windows



TECHNICAL DATA

	Material	Engineered fingerjointed pine, selected pine, meranti, oak, other on request, laminated.		
Uw	Uw value	1.3 W/m²K (for test size window 1230x1480mm)		
	Glazing package, Ug value	24mm (4-16-4), Ug = 1,1 W/m²K / 32mm (4-10-4-10-4) Ug = 0,8 W/m²K Glass package may be modified.		
\Diamond	Air permeability	Class 2		
000	Watertightness	Class 2A		
ဂျို	Wind load	Class C3		
₫P	Fittings	IPA, PN		
7	Surface treatment	Transparent colours based on current colour chart. Opaque colours based on RAL and NCS charts.		

***** DIMENSIONAL RANGE

Hinge type	Min frame width	Max frame width	Min frame height	Max frame height	
п типде сурс				Windows	French door
Side swing	475	975	393	1700	2450
Side hung	360	893	393	1700	2450

